

FANCOIL MURAL

MODELO **KFCI-SP**

R05BGE



| CARACTERÍSTICAS | | 250 | 400 | 600 |
|------------------------------------|----------|----------------|----------------|---------------|
| CAPACIDAD FRIGORÍFICA 7/12 (L-M-H) | KW | 1,97/2,2/2,63 | 2,66/2,9/3,28 | 3,21/3,95/5,0 |
| | Frig/h | 2.261 | 2.820 | 4.300 |
| CAPACIDAD CALORÍFICA 50/40 (L-M-H) | KW | 2,35/2,85/3,36 | 3,35/3,77/4,37 | 4,18/5,17/6,7 |
| | Kcal/h | 2.890 | 3.758 | 5.762 |
| MOTOR VENTILADOR | | | | |
| CAUDAL AIRE (L-M-H) | m³/h | 320/410/425 | 504/550/680 | 670/820/1.020 |
| ALIMENTACIÓN | V-ph-Hz | 220/240-1-50 | | |
| VELOCIDADES | Nº | 3 | 3 | 3 |
| POTENCIA ABSORBIDA MÁXIMA (H) | W | 10,7 | 33 | 37,5 |
| CORRIENTE FUNCIONAMIENTO | A | 0,05 | 0,10 | 0,14 |
| NIVEL POTENCIA SONORA (L-M-H) | dB(A) | 28/31/34 | 35,2/37,3/41,5 | 35,9/41/45 |
| NIVEL PRESIÓN SONORA (L-M-H) | dB(A) | 23/26/30 | 29/32/36 | 31/36/40 |
| INSTALACIÓN | | | | |
| CONEXIONADO TUBO AGUA | Pulgadas | 3/4 | 3/4 | 3/4 |
| PÉRDIDA CARGA BAT. AGUA FRIA (H) | kPa | 23,1 | 42 | 36,3 |
| CAUDAL AGUA | L/H | 452 | 564 | 860 |
| CONEXIÓN DIÁMETRO DESAGÜE | mm | 20 | 20 | 20 |
| BOMBA DE CONDENSADOS | | No | No | No |
| DIMENSIONES | | | | |
| PROFUNDO | mm | 230 | 230 | 230 |
| ALTO | mm | 290 | 290 | 315 |
| ANCHO | mm | 915 | 915 | 1.072 |
| PESO NETO | Kg | 12,7 | 12,7 | 12,7 |
| CÓDIGO | | 0190040012 | 0190040014 | 0190040016 |

DIMENSIONES DE LA UNIDAD

